Contractor	Unkno	n	Address
Date <u>driller</u>	Dug.	1.884	Elev. above sea level top of wel
Depth 30 ft	t •		s y
then	thru str	ata of substan	then thru ist layer of sandstone, ce unknown and then into 2nd layer
Were drill cut	tings saved_	• • • • • •	Where filed
Size hole_4	<u>ft.</u> If	reduced, where ar	nd how much Not reduced
Casing record	Rock.	lonc. curb and	board top 2 ft. above grade.
Distance to wa	ater when no	t pumping15_f	t. Distance to water is
feet after pun	nping at		G. P. M. forhours.
Reference poi	nt for above	measurements	Grade
Type of pump	Red Jac	cet.& Myers Ja	ck.Distance to cylinder 8 ft.
Length of cyl	inder_12"_;	C_3"1/2" dla	Length of suction pipe below cylinder 20 ft.
Length stroke.	4"		Speed 40
Hours used po	er day <u>2</u>		Type of powerElectric
Rating of mo	tor	/3 hp.	Rating of pump in G. P. M. 6.5
Can following	be measure	i: (1) Static wate	er level
(2) Pumping	level No.	¥ ————————————————————————————————————	(3) Discharge18 [#]
(4) Influence	on other wel	lsNone	
Temperature (of water	18_degF	Was water sample collectedNo
Date			Effect of water on meters, hot water
coils, etc		Unknown	<u> </u>
Date of Analy	8is		Analysis No
	*	+	RecorderC_L_Jacobs
::807-10399 12 -			DateFeb. 15_1934

Water is clear and has no odor or taste. Is used only for water-ing stock. 50 hd. cattle.

Quantity of water varies with the seasons but the well has never gone dry.

When the well was first dug the spning, located about 400 ft. South West, went dry for about 30 days and then gradually regained its flow.

For location of well and spring see sheet # 1.


	The state of the state of the state of		
		• • • • • • • • • • • • • • • • • • • •	
· · · · · · · · · · · · · · · · · · ·	Andrew State of the State of th	 Fig. 1. Supplies the second of the second of	
		· · · · · · · · · · · · · · · · · · ·	,
	* * * * * * * * * * * * * * * * * * *	order to the second of the second of the second	•
		All the second of the second of the second	
	• * * •	the first state are as a second of the	
	en e		
	; + e*	the state of the s	
	e in the sign of the sign being the sign of	And the state of t	
	Compared to a digree	The the state of the state of the state of	
	All the state of t		
	ी का ज <mark>न्म जैन रह</mark> ी	tolographic states	
	e en activista francis (f. 1	• for the second of the end of the second	
	• 1	en en Might in transporter and the armount	
		gradient was de la service de la companya del companya de la compa	
		. e table in the second configuration.	
		ight.	
		gar 🐒 - alika jarjan	
	e 💢 et e je wit	en e	
	t in the second		

Owner John G. Eisele	AuthoritySame
Contractor John G. Eisele	Address Same
Date drilled_Dug. 1919	Elev. above sea level top of well
Depth 32 ft.	
Log Top soil (Black Loam) 6" y ye	llow clay to 10 ft., sandy loam and clay
to 13 1/2 ft., gravel and 1: 25 1/2 ft., blue clay and se	imestone to 21 1/2 ft., solid limestone to
Were drill cuttings saved No	
Size hole 4 1/2 ft. If reduced, where a	Reduced at 21 1/2 ft., gradual and how much taper to 2.ft. at 32 ft.
Casing record Brick. Conc. top fl	ush with grade.
Distance to water when not pumping 25	Distance to water is
feet after pumping at	G. P. M. for hours.
Reference point for above measurements	Grade
Type of pump Barnes	Distance to cylinder 27 ft.
	Length of suction pipe below cylinder 4 ft.
Length stroke 6"	Speed40
Hours used per day 1/4	Type of powerHand
Rating of motor	Rating of pump in G. P. M. 12
Can following be measured: (1) Static wat	ter level25_ft.
•	(3) Discharge2 ft.
(4) Influence on other wells None	
Temperature of water 50 deg. F.	Was water sample collectedNo
Date	Effect of water on meters, het water
Forms considerable	Lime.
	,
Date of Analysis	Analysis No.
:	Recorder
2807-10309 12	DateFeb.14_1934

Water is clear and has no odor or taste. Is used only for crinking. 7 persons in family.

Well can be pumped dry and will refill in about 2 or 3 days. However it has never gone dry in ordinary use. Stock water from spring and other well, see sheet # 2 for other well.

Both springs flow continuously the year around at about 2 (1.P.M. The spring water can be seen coming from cracks in the Lime-stone.



	or variable of the state of th
City Rural Route # 2. Hanna City	CountyPeoria
Section 31 Kickapoo Twp. No.	T 9 N Range R 7 E
Location (in feet from section corner) 30 f	ft.South of N.line and 120 ft.West of gravel road along 1/2 Sec. 1
Owner Howarth School	Authority Walter Taylor (Direction
Centractor Unknown	Address
Date driffed Dug. 1911	Elev. above sea level top of well
Depth 17 ft.	
Log All clay down to # 7 ve	in soft coal. Bottom of well is an
	Where filed
	and how much Not reduced
	and board top 6" above grade.
	1 ft. Distance to water is
Distance to water when not pumping.	
feet after pumping at	G. P. M. for
feet after pumping at Reference point for above measurements	G. P. M. for Top of well.
feet after pumping at Reference point for above measurements Type of pump No pump in place.	G. P. M. for Top of well. Distance to cylinder
feet after pumping at Reference point for above measurements Type of pump No pump in place. Length of cylinder	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder
Reference point for above measurements Type of pump No pump in place. Length of cylinder	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used.	G. P. M. for
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder Speed Type of power Rating of pump in G. P. M.
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder Speed Type of power Rating of pump in G. P. M.
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder Speed Type of power Rating of pump in G. P. M.
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa (2) Pumping level No.	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder Speed Type of power Rating of pump in G. P. M.
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa (2) Pumping level No. (4) Influence on other wells None	G. P. M. for Top of well. Distance to cylinder Length of suction pipe below cylinder Speed Type of power Rating of pump in G. P. M. ater level 11 ft. (3) Discharge No.
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa (2) Pumping level No. (4) Influence on other wells None Temperature of water 50 deg.F.	G. P. M. for
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa (2) Pumping level No. (4) Influence on other wells None Temperature of water 50 deg.F.	G. P. M. for
Reference point for above measurements Type of pump No pump in place. Length of cylinder Length stroke Hours used per dayNot used. Rating of motor Can following be measured: (1) Static wa (2) Pumping level No. (4) Influence on other wells None Temperature of water Date coils, etc. Unknown	G. P. M. for

Water has not been used from this well for past 10 years, account of decided sulphide odor and taste. The school children would not drink it. About 2 years ago the pump was stolen and has not been replaced.

Water for school use is carried from well contained in report #

49.04.00 Control Control Tailets 120 The attended 1 Berton or the larger of given 4,11

at always by west

rolling 1

: :

Contractor John G. Elsele	AddressSame
Date drilled Dug. 1933	Elev. above sea level top of well
Depth 27 ft.	
Leg Same as sheet # 1.	· · · · · · · · · · · · · · · · · · ·
Were drill cuttings saved No.	Where filed
Size hole 5 ft. If reduced, where a	nd how much Not reduced.
Casing record Brick. Conc. top 6"	above grade.
Distance to water when not pumping 20	ft. Distance to water is 26 1/2 ft.
feet after pumping at 18	G. P. M. for 4 hours.
Reference point for above measurements	Top of well.
Type of pump Hayes Double Action	Distance to cylinder8 ft.
Length of cylinder 12" x 3" dia.	Length of suction pipe below cylinder_18_1/2_ft
Length stroke 8"	Speed40
Hours used per day 1/4.	Type of powerHand
Rating of motor	Rating of pump in G. P. M. 18
Can following be measured: (1) Static wat	er level
(2) Pumping levelNo.	(3) Discharge30**
(4) Influence on other wells None	
Temperature of water 50 deg. F.	Was water sample collectedNo.
Date	Effect of water on meters, hot water
ccils, etcUnknown	
Date of Analysis	Analysis No
•	Recorder_C.L.Jacobs
2807-19390 12	DateFeb. 14 1934

Water is clear and has no odor or taste. Is used only for watering stock. 13 sheep, 20 cattle, 29 hogs and 6 horses. The stock however water mostly from the spring.

The quantity of water in this well varies considerably with the seasons.

On one occasion, after pumping steadily for 4 hrs. the water was lowered to the end of the suction pipe but the water kept flowing into the well so rapidly that the pump had to kept in operation to hold the water at that level.

Well has never gone dry.

For location see sheet # 1.

Contract to The form of the second of the second of And the second of the second o and the second of the second of the second many and the first of Commence of the second A Charles Same The state of the probability and the second Astronomic Const signer been might Committee the second . Programme A section of major 2 may the Care of and maintain of male Commence of the Commence of th · Committee the state of the st in the second of the second of the The Control of the San St. • The sale of the control of the con

en ing panganan ang kalangan Maria. Panganan ang kalangan Maria

Att Commence

200 5 4 4 70 447 TALL

2121 W/A 3 2 4 1

. 1.1

ILLINOIS DEPARTMENT OF PUBLIC HEALTH WELL CONSTRUCTION REPORT

1.	Type of Well				
		Bored Hol	e Diamin	. Depth	_ft.
	Curb materia	ıl Bu	ried Slab: Yes_	No	
	b. Driven	Drive Pipe	Diamin.	Depth	_ft.
	c. Drilled	Finished in	n Drift	In Rock	·
		Gravel Pac			
	d. Grout:				
		(KIND)	FROM (Ft.)	TO (Ft.)	
		B. r. P Suche		27 (3	
	Distance to Ne			_	
	Building 20		Seepage Tile Fic	14	
7.77.	Cess Pool		Sewer (non Cast		
	Privy		Sewer (Cast iron	, -	
	Septic Tank		Barnyard		
	Leaching Pit		Manure Pile		
3	-	nis well to be use			
	V 1 -	NT-		_	
. Δ	Date well comp	leted 7.4-2	1, 1967		
. .	Darmanant Dum	p Installed? Y		No 1	
٥.	Manufacturer	p installed r	Type	110	
		gpm. Dept			ft
	Well Ten Sanla	d? Yes	No.		_ ***
٥.	men Top Segre	or les <u>ca</u>			
7.	Pittess Adapto	r Installed? Yedd? Yes	,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,, ,,	°	
9.	Water Sample S	ubmitted? Yes	P	io <i></i>	
	Lounn w	telaubon	it water	Samoele	
	MARKS:			<u> </u>	
-1	/	l won	11-11 11	7 /	
1-3	mu vice	A ROOM	Color Color	د یک سکیسیم	72.2.
ر کر	and lessol	the wit	ditus	Contract 1	All Billion
/0	يوكم فرتين سعسان	I Scherren	300 B 20	marin R	sea distant
<u>-</u> ِ ٔ	/			1	- agatin
フェ	winner.	that fu	" mund		
مهدوسة	ون سعید سامید	miliar pu	and the bank	13 1000	are and
					، ہے۔

GEOLOGICAL WATER SURVEYS WATER WELL RECORD

10. Non Responsive - per	sonal pr	ivacy	information
12. Water from Carre Mile Court	-13 Count	NO.	00 L
Formation			Companies .
at depth // 7 toft. 14. Screen: Diamin. Length:ft. Slot	_		@
15. Casing and Liner Pipe	,		
Diam. (in.) Kind and Weight	From (Ft.)	To (Ft.)	SHOW
6 3 Contiden (18.92)	0	47	LOCATION IN SECTION PLAT
G M.G. PASA [18.41]			
17. Static level 20 ft. below casi above ground level. Pumping lev gpm for 1 hours.	rel 37 ft.	when pu	nping at
	СН	THICK	NESS DEPTH OF
18. FORMATIONS PASSED THROUGH	сн	THICK	NESS DEPTH OF BOTTOM
18. FORMATIONS PASSED THROUGH	сн	THICK!	19
18. FORMATIONS PASSED THROUGH	сн	/ / / / / / / / / / / / / / / / / / /	NESS DEPTH OF BOTTOM
18. FORMATIONS PASSED THROUGH	сн	22 / 55	19
18. FORMATIONS PASSED THROUGH	сн	22 / 55	19
18. FORMATIONS PASSED THROUGH	сн	22 / 55	19
18. FORMATIONS PASSED THROUGH	сн	22 / 55	19
18. FORMATIONS PASSED THROUGH	сн	22 / 55	19
18. FORMATIONS PASSED THROUGH	СН	22 / 55	19
18. FORMATIONS PASSED THROUGH		22 / 55	19

LOG OF WATER WELL

Property owner Drilled by W.S. Hofstetter-Peoria Thick-Depth of Bottom Formations passed through Yellow Clay 25 25 Yellow Sandstone 10 35 Gray Shale 65 30 Gray Shale 65 inch Black Steel Casing from 0 to Cased with _inch. Static level from surf_ Size hole below casing. Tested capacity_ _gal. per min. Temperature. Water lowered to. Length of test min. Screen. Length Bottom set at Peoria County_

Index:

Copy for Illinois State Water Survey

City_

Section

Location	
Owner	
Contractor Unknown	Address
Date drilled- Dug. 1859	Elev. above sea level top of well
Depth 18 ft.	
Log Clay to 6 ft., clay and sand	l rock to bottom of well.
Were drill cuttings saved	Where filed
Size hole 4 ft. If reduced, where and	how much Not reduced
Casing record Rock. Conc. curb and	board top 2 ft. above grade.
Distance to water when not pumping 15 ft.	Distance to water is
feet after pumping at	_G. P. M. forhours.
Reference point for above measurements	Grade
Type of pump Red Jacket	Distance to cylinder 4 ft.
Length of cylinder 12" x 3 1/2" dia.	Length of suction pipe below cylinder 13 1/2 ft.
Length stroke 6"	Speed40
Hours used per day 1/4	_Type of powerHand
Rating of motor	Rating of pump in G. P. M. 10
Can following be measured: (1) Static water	level15_ft.
(2) Pumping level No.	_(3) Discharge18"
(4) Influence on other wells None	
Temperature of water 48 deg. F.	_Was water sample collectedNo
	Effect of water on meters, het water
coils, etcUnknown	
Date of Analysis	Analysis No
<i>,</i>	RecorderC.L.Jacobs
2807-19399 12	DateFeb15_1934

Water is clear and has no odor or taste. Is used only for watering stock.

Quantity of water varies with the season but the well has never been dry.

For location see sheet.# 1.

A september of the second of t

• The state of the

Support to the second of the se

White the second of the second of the second of the

• secolar of exact to the second seco

and the first of the state of the first term is a second of the state of the state

The state of the s

and the state of the second second

The group to a street the second seco

Lead into a stell (1) a floring a coding a self-of-

englighted the control of the contro

the state of the s

The second teacher of the second seco

order in the transported of the control of the cont

 \mathcal{C}_{ij}

The Control of the Arman Control of the Control of


 $q x^{\alpha}$. It

and the second s

Contractor	Address
Date drilled Dug. 1855	Elev. above sea level top of well
Depth 48 ft.	
Log Unknown. Bottom of well	not far from #6 vein of coal.
Were drill cuttings saved	Where filed
Size hole 3 ft. If reduced, where a	and how much Not reduced
Casing record Rock. Conc. curb	and board top 8" above grade.
Distance to water when not pumping 33	ft. Distance to water is
feet after pumping at	G. P. M. for hours.
Reference point for above measurements	Top of well
Type of pump_F.E.Hyers	Distance to cylinder35 ft.
Length of cylinder 12" x 3" dia.	Length of suction pipe below cylinder 2:0 ft.
Length stroke 6"	Speed40
Hours used per day 1/4	Type of powerHand
Rating of motor	Rating of pump in G. P. M. 7
Can following be measured: (1) Static wat	er level33_ft.
(2) Pumping levelNo	(3) Discharge12"
(4) Influence on other wells None	
Temperature of water 50 deg. F.	Was water sample collectedNo
Date	Effect of water on meters, hot water
coils, etc. Extremely hard, for	me much Lime.
Date of Analysis	Analysis No
•	RecorderC.IJacobs
2807-10399 12	Date Feb. 15 1934

Water is clear and has no odor or taste. Is used only for drinking. 5 persons in family.

Well has never gone dry and cannot be pumped dry with the present pump.



Strain / But St

Non Responsive - per	sonal privacy information—
Section	_
Locati	_
Owner	
Contractor Unknown	Address
Date drilled Dug. 1910	Elev. above sea level top of well
Depth 35 ft.	
LogAll clay.	
Were drill cuttings saved	_Where filed
Size hole 3 ft. If reduced, where and	how much Not reduced
Casing record Brick. Conc. and board	top 6" above grade.
Distance to water when not pumping 20 1/2	ft. Distance to water is
feet after pumping at	_G. P. M. forhours.
Reference point for above measurements	Top of well.
Type of pump No name on pump.	Distance to cylinder 4 ft.
Length of cylinder 12" x 2" dia.	Length of suction pipe below cylinder 28 ft.
Length stroke6"	Speed 40
Hours used per day 1/4	_Type of powerHand
Rating of motor	Rating of pump in G. P. M.
Can following be measured: (1) Static water i	evel20_1/2_ft
(2) Pumping level No.	_(3) Discharge18 ⁿ
(4) Influence on other wells None	
Temperature of water 50 deg. F.	_Was water sample collectedNo
Date	Effect of water on meters, het water
coils, etc. Forms Lime	
Date of Analysis	Analysis No.
•	RecorderC.L.Jacobs
2807-19309 12	Date Feb. 14 1934

Water is clear and has no odor or taste. Is used only for drinking. 2 persons in family and water is carried from here to school house. See report # for school house.

The well can be pumped dry and sometimes goes dry ear in ordinary use.

Stock water from spring-fed creek located about 20 rods East of well.

N 100 to a not found to be in graphy gra enter mili k

Section Commence

1.65

1 1 to 3 to 3 to 3

490 33 35 35